

取扱材料リスト

名北工業(株)

材質	規格	線材 (Wire)	棒材 (Bar)				メーカー
			丸	六角	異形	センター	
低合金鋼	SAE8740	AMS-S-6049 AMS-6322 MIL-S-6049	●	●	●	●	Republic steel Corp. (アメリカ オハイオ州)
析出硬化系 ステンレス	15-5PH Type1 ST 15-5PH Type2 ST 15-5PH H1025	AMS-5659		●			○
	17-4PH Solution 17-4PH H1025 17-4PH H1150	AMS-5643		●			○
オーステナイト系 ステンレス	303 CRES/304 CRES	AMS-5640/ AMS-5639 AMS-5647 AMS-QQ-S-763		○			○
マルテンサイト系 ステンレス	440C CRES	AMS-5618 AMS-5630 AMS-QQ-S-763		○			
フェライト系 ステンレス	430 CRES	AMS-5627 AMS-QQ-S-763		○			
耐熱鋼	A286	AMS-5731 AMS-5732 AMS-5737		○			
アルミ	7075 T7351 7075 T73511	AMS-QQ-A-200/11 AMS-QQ-A-225/9		○			YE FONG ALUMINIUM INDUSTRIAL LTD. (台湾 桃園市)
チタン	Ti 6AL-4V	AMS4928		○			VSMPO-AVISA Corp. (ロシア)

※ ●：販売実績有り ○：取扱可能（別途御相談承ります）
※ 記載内容は一例です。詳細についてはお問い合わせください。

★棒材の切断対応可能です。（切断可能長さ：10mm～2,000mm）

PH鋼 在庫リスト

:新規在庫品

材質	熱処理 状態	規格	サイズ		定尺材(≒3,000mm) 本数	端材	
			(mm)	(inch)		長さ(mm)	本数
15-5PH(VAR)	TYPE1	AMS 5659R	31.750	1.250	13		
15-5PH(VAR)	TYPE1	AMS 5659R	53.975	2.125	0	2,767	1
15-5PH(ESR)	TYPE2	AMS 5659R	41.275	1.625	12	1,500	1
15-5PH(ESR)	TYPE2	AMS 5659R	44.450	1.750	4	1,449	1
15-5PH(VAR)H1025	H1025	AMS 5659R	15.875	0.625	23	2,597	1
						2,653	1
15-5PH(VAR)H1025	H1025	AMS 5659R	31.750	1.250	19	859	1
15-5PH(VAR)H1025	H1025	AMS 5659R	50.800	2.000	8	1,594	1
17-4PH	Solution	AMS 5643T	9.525	0.375	29	2,132	1
						2,150	1
						2,342	1
17-4PH	Solution	AMS 5643T	12.700	0.500	0	875	1
						1,084	1
						2,367	1
17-4PH	Solution	AMS 5643T	17.526	0.690	47	2,645	1
						2,653	1
17-4PH	Solution	AMS 5643T	25.400	1.000	0	2,366	1
17-4PH	Solution	AMS 5643T	31.750	1.250	2	2,577	1
						2,607	1
						2,609	1
						1,500	1
17-4PH	Solution	AMS 5643T	50.800	2.000	7	1,377	1
						2,722	1
						2,726	1
17-4PH	Solution	AMS 5643T	57.150	2.250	1	936	1
						943	1
						959	1
						969	1
17-4PH	Solution	AMS 5643T	63.500	2.500	3	1,000	1
						1,446	1
17-4PH(H1025)	H1025	AMS 5643T	25.400	1.000	36	2,425	1
						2,705	1
						2,720	1
17-4PH(H1025)	H1025	AMS 5643T	31.750	1.250	29	2,083	1
						2,533	1
17-4PH(H1025)	H1025	AMS 5643T	38.100	1.500	17	2,542	1
17-4PH(H1025)	H1025	AMS 5643T	50.800	2.000	9	2,088	1
17-4PH(H1150)	H1150	AMS 5643T	9.525	0.375	202	2,749	1
						2,755	1
						1,800	2
						1,200	2
17-4PH(H1150)	H1150	AMS 5643T	50.800	2.000	12	2,622	1
						2,645	1
17-4PH(H1150)	H1150	AMS 5643T	57.150	2.250	2	2,681	1
						2,584	1
						2,587	1

材質	熱処理 状態	規格	サイズ		定尺材(12ft) 本数	端材	
			(mm)	(inch)		長さ(mm)	本数
15-5PH(VAR)	TYPE1	AMS 5659S	15.880	0.625	131		
15-5PH(VAR)	TYPE1	AMS 5659S	19.050	0.750	128		
15-5PH(VAR)	TYPE1	AMS 5659S	22.230	0.875	62		
15-5PH(VAR)	TYPE1	AMS 5659S	25.400	1.000	250		
15-5PH(VAR)	TYPE1	AMS 5659S	28.580	1.125	61	3,209	1
15-5PH(VAR)	TYPE1	AMS 5659S	31.750	1.250	44		
15-5PH(VAR)	TYPE1	AMS 5659S	34.930	1.375	50		
15-5PH(VAR)	TYPE1	AMS 5659S	38.100	1.500	44		
15-5PH(VAR)	TYPE1	AMS 5659S	41.280	1.625	10		
15-5PH(VAR)	TYPE1	AMS 5659S	44.450	1.750	22		
15-5PH(VAR)	TYPE1	AMS 5659S	50.800	2.000	41		
15-5PH(VAR)	TYPE1	AMS 5659S	57.150	2.250	14	1,820	1
15-5PH(VAR)	TYPE1	AMS 5659S	60.330	2.375	18		
15-5PH(VAR)	TYPE1	AMS 5659S	63.500	2.500	12		
15-5PH(VAR)	TYPE1	AMS 5659S	69.850	2.750	73		
15-5PH(VAR)	TYPE1	AMS 5659S	82.550	3.250	26		
15-5PH(VAR)	TYPE1	AMS 5659S	95.250	3.750	8		
15-5PH(VAR)	TYPE1	AMS 5659S	108.000	4.252	5		
15-5PH(ESR)	TYPE2	AMS 5659S	44.450	1.750	10	2,504	1
15-5PH(VAR)H1025	H1025	AMS 5659S	15.875	0.625	38		
15-5PH(VAR)H1025	H1025	AMS 5659S	25.400	1.000	94		
17-4PH	Solution	AMS 5643V	10.000	0.394	239		
17-4PH	Solution	AMS 5643V	12.700	0.500	212		
17-4PH	Solution	AMS 5643V	15.870	0.625	86		
17-4PH	Solution	AMS 5643V	19.050	0.750	57	1,800	1
17-4PH	Solution	AMS 5643V	22.225	0.875	60		
17-4PH	Solution	AMS 5643V	25.400	1.000	38		
17-4PH	Solution	AMS 5643V	38.100	1.500	25		
17-4PH	Solution	AMS 5643V	45.000	1.772	18		
17-4PH	Solution	AMS 5643V	47.620	1.875	10		
17-4PH	Solution	AMS 5643V	57.150	2.250	10		
17-4PH	Solution	AMS 5643V	69.850	2.750	6		
17-4PH	Solution	AMS 5643V	95.250	3.750	0	2,500	1
17-4PH	Solution	AMS 5643V	101.600	4.000	1		
17-4PH(H1025)	H1025	AMS 5643V	25.400	1.000	130		
17-4PH(H1025)	H1025	AMS 5643V	31.750	1.250	68		
17-4PH(H1025)	H1025	AMS 5643V	38.100	1.500	19		
17-4PH(H1025)	H1025	AMS 5643V	50.800	2.000	7		